



<b>EKO - CK</b>		<b>20</b>	<b>25</b>	<b>30</b>	<b>35</b>	<b>40</b>	<b>50</b>	<b>70</b>	<b>90</b>	<b>110</b>
Toplinski učin	(kW)	15-20	20-25	25-30	30-35	35-40	40-50	50-70	70-90	90-110
Sadržaj vode u kotlu	(l)	76	81	90	96	101	114	175	193	214
Masa kotla	(kg)	253	260	282	293	320	348	395	423	451
Promjer* / visina (l) dimnjače	φ(mm)	150/910	150/910	160/910	160/910	180/900	180/900	200/975	200/975	200/975
Otvor za plamenik	φ(mm)	105	105	105	105	105	105	105	105	105
Potlak dimnjaka	(Pa)	16	20	21	22	23	24	27	30	32
Polazni/povratni vod	(R)	5/4"	5/4"	5/4"	5/4"	5/4"	5/4"	5/4"	5/4"	5/4"
Punjenje/pražnjenje	(R)	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Sigurnosni vod	(R)	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	1"	1"	1"
Temp. dimnih plinova	(°C)	200	200	200	200	200	200	200	200	200
Max. radna temperatura	(°C)	90	90	90	90	90	90	90	90	90
Max. radni pretlak	(bar)	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5
Dubina kotla A	(mm)	1020	1055	1055	1055	1055	1130	1250	1250	1250
Visina kotla B	(mm)	1200	1200	1200	1200	1200	1200	1335	1335	1335
Širina tijela kotla C	(mm)	430	430	480	530	580	580	580	630	680
Ukupna širina kotla D	(mm)	526	526	576	626	676	676	676	726	776
Visine (E / F)	(mm)	80/480	80/480	80/480	80/480	80/480	80/480	120/500	120/500	120/500
Visina G	(mm)	1070	1070	1070	1070	1070	1070	1170	1170	1170
Max. dužina cjepanice	(mm)	500	500	550	550	550	550	550	550	550

Klikni za zatvaranje slike, Klikni i vuci za premještanje. Klikni na strelice na tipkovnici za sljedeću i prethodnu sliku.

